

## Transmax Agri MP Plus 10W-30

Super universal tractor oil

### Description

One oil that delivers high performance & protection for engine, transmission, wet brake, hydraulic and front axles.

### Advantages

- One oil simplifies servicing, avoiding misapplication
- One oil reduces inventory, saving money
- Excellent cold start protection reduces engine wear

### Typical Characteristics

Name	Method	Units	Transmax Agri MP Plus 10W-30
Density @ 15C, Relative	ASTM D1298	g/ml	0.872
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	11.60
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	79
Viscosity Index	ASTM D2270	None	140
Viscosity, CCS -20C	ASTM D5293	mPa.s (cP)	3300
Viscosity, CCS -25C	ASTM D5293	mPa.s (cP)	6200
Viscosity, Brookfield @ -18C	ASTM D2983	mPa.s (cP)	4820
Pour Point	ASTM D97	°C	-45
Flash Point, COC	ASTM D92	°C	242

## Product Performance Claims

API GL-4

API CF-4/SF

MF - M1145

ZF TE-ML 06B(\*), 07B

Meets MF M1139, MF M1144, JD J27, Ford M2C 159-B

Suitable for use where JD 20C, Ford M2C-134D and 86B, Case MS 1207 are specified

## Additional Information

Transmax Agri MP Plus 10W-30 is registered under the following ZF approval number: ZF003416

Transmax Agri MP Plus 10W-30

18 Jul 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

[www.castrol.com](http://www.castrol.com)